


cyl. D 4
 Sn = 1,5 mm
 DC 3-Wire
 shielded



PX0855



1 2 3



Utilization categories DC 13

Further information:



Einbauhinweise 825357



Hinweis EMV Schutzbeschaltung

Common Data

Mounting		shielded
Rated operating distance Sn	mm	1,5
Assured operating distance Sa	mm	0...1.2
Repeatability	%	<= 5
Hysteresis	%	<= 15
Function Indication		yes
Ambient temperature range	°C	-25...+70
Polution Degree		3
IEC-Code		I1B04BN2
Time delay before availability	ms	<= 10

Mechanical Data

Housing size	mm	cyl. D 4
Measurements BxHxT or DxT	mm	D4 x 41
Housing material		stainless steel
Material of sensing face		POM
Degree of protection		IP67
Connection		Connector S49

Electrical Data

Current type		DC
Wiring		3-Wire
switching function		normally-closed
Output signal		NPN
Rated operational voltage	V	24 DC
Rated operational current	mA	100
Supply voltage	V	10...30 DC
Ripple	%	<= 10
Rated supply frequency	Hz	1800
Minimum operational current	mA	0
No-load supply current	mA	<= 10/<= 3
Off-state current	µA	<= 80
Voltage drop	V	<= 3.0/-
Short circuit protection		yes
Protected against polarity reversal		yes

EMV

ESD/RFI/Burst/IVW

Emission

21.01.2004 / Online-Information

If not differently indicated,
 all values by IEC 60947-5-2 (DIN EN60947-5-2)

Specifications subject to change

Balluff GmbH
 Postfach 1160
 73761 Neuhausen
 Telefon (07158) 173-0
 Telefax (07158) 5010

