Optoelectronic Sensors
BGL 20A-002-S 49

Fork-thru-beam
40x49x10
slot wide=20mm





PX1494

Common Data

Sensortype		Fork-thru-beam
Switching frequence		1500 Hz
slot width	mm	20
Repeat accuracy		0,02mm
Hysteresis		≤0,1mm
Resolution	mm	0,3
Indication switching element		yes, red LED
Ambient temperature	°C	-10...+60
Light		Red light 640nm
Sensitivity adjustment		Poti: 0...270°
Permissable ambient light	lux	10000

Mechanical Data

Measurements BxHxT or DxT	mm	40x49x10
Housing material		anodized aluminium
Material of sensing face		Glass
Degree of protection	IP	65
Connection		Connector S49 (M8 3-pin)
Weight		28g
Recommended connector		BKS-S 48/BKS-S 49

Electric Data

Current		DC
Switching function		NO/NC switchable
Output		NPN
Rated operational voltage Ue	V	24 DC
Rated operational current Ie	mA	200
Supply voltage	V	10-30 DC
No-load supply current	mA	≤35
Voltage drop	V	<2,5
Short protection		yes
Protectde against polarity rev		yes

Approvals

CE

Utilization categories DC13

If not differently indicated,
all values by IEC 947-5-2 (DIN EN60947-5-2)

Specifications subject to change

Balluff GmbH
Postfach 1160
73761 Neuhausen
Telefon (07158) 173-0
Telefax (07158) 5010

03.06.2004 / Online-Information

Casp System Sp. Z o.o., Puszkina 2, 43-603 Jaworzno, Polska, www.casp.pl, e-mail: biuro@casp.pl, tel/fax: +48 32 614 09 17